



06-01

Mississippi State Highway Department / P.O. Box 1850 / Jackson, Mississippi 39215-1850 / FAX (601) 359-2233

May 6, 1991

ASPHALT

TO: Districts  
Divisions

FROM: James D. Quin  
Chief Engineer

SUBJECT: Pavement Striping

The Department has adopted the following policy for pavement striping on all facilities with 2000 ADT or more.

1. Center lines, lane lines and detail stripe will be 90 mil thermoplastic.
2. Edge lines will be 60 mil thermoplastic.
3. Legend, including railroad markings, pedestrian crosswalks and stop lines, will be 120 mil thermoplastic.

Facilities with low traffic counts will remain as currently set out.

All projects requiring new striping will be prepared accordingly. Proposals will indicate the acceptable cold plastic alternates allowed by the Department. Maintenance of old stripes on their original surface will be of the same type material initially placed except that paint will be permitted if the facility is to be re-surfaced within three years.

Variances of this policy must be approved by this office.

JDQ:RLH:lf

IMPLEMENT FOR JULY LETTING.

WTR

**RECEIVED**

**MAY 7 1991**

ROADWAY DESIGN

ROADWAY DESIGN		
	Action	Info
RIJFF	✓	RLH
HARRIS		JA
BALENTINE		
HENLEY		
PICKERING		
SMITH		
WHITFIELD		
FORTUNE		
SMITH		
NOLAN		