

Pickering, John

From: Pickering, John

Sent: Friday, November 15, 2002 11:39 AM

To: Ruff, Wendel; McMahan, Steve; Portera, Joy; Swindoll, William; Broome, Darrell (Distric 7 Engr.); Dickerson, Jimmy; Lee, Richard; Lyons, Walter; May, Ricky

Cc: Purvis, Keith; Reeves, Steve; Whitfield, Robert; Amy Mood; Brad Fletcher; David Seal; Reese, John; Richard Pittman

Subject: Change Type of Right of Way Markers Normally Used

Roadway Design Division has been advised by the 10th floor administration to change the type of Right of Way Markers normally used from Type I to Type II. The Type I marker is installed 8" above ground and the Type II marker is installed 1" above ground, except it will be placed flush where the marker is installed within a paved or sidewalk area.

All plans will require the Type II marker beginning with the January, 2003 letting, regardless of whether or not they have been small-blued. It is my understanding the only change to the plans will be the use of a "907" and revise the Type I to Type II.

The markers will be required to be installed by a licensed surveyor according to minimum surveying standards. This requirement should be stated in the specifications, thus the "907" requirement. This requirement should be handled by Construction Division.

John B. Pickering

Roadway Design Division Engineer

Mississippi Department of Transportation

Phone: (601) 359-7257

Fax: (601) 359-7063

E-Mail: jpickering@mdot.state.ms.us